

MiraSeal™ 511 Porous Plus

Natural Look Penetrating Sealer

Water, Stain & Slip Protection for

- Grout
- Limestone
- Flamed & Honed Granite
- Saltillo Tile
- Terra Cotta Pavers
- Masonry
- Sandstone
- Porous Slate & Brick
- Textured Marble
- Cement
- Concrete
- Cantera/Adoquin
- Flagstone
- Sanded Grout
- Stucco

Uses

- Interior & Exterior
- Kitchens
- Showers
- Restrooms
- Patios
- Drive Ways
- Garages
- Pool Areas
- Walls

Special Features

- Water Resistant
- Stain Resistant
- Weather Resistant
- Acid Resistant
- Salt Resistant
- Freeze/Thaw Resistant
- Slip Resistant
- Easy To Use
- Low Toxicity
- Nonyellowing
- Noncoating
- U.V. Transparent

Product Description

KEEP OUT OF REACH OF CHILDREN. 511 Porous Plus is a unique formulation designed for the protection of all porous tile, stone and grout surfaces. 511 Porous Plus penetrates into the surface and forms an invisible barrier that is resistant to moisture and stains, while allowing vapor to escape. 511 Porous Plus is not a surface coating and will not alter the natural look. All surfaces are harder and less slippery. 511 Porous Plus can be used on interior and exterior applications from -65° F to 400° F. 511 Porous Plus is U.V. transparent, resists acid rain and will not yellow under any circumstances. 511 Porous Plus averages 2 to 5 times the coverage of competitive products. (See coverage chart).

511 Porous Plus is on the approved sources list of the United States Postal Service and is U.S.D.A. approved for incidental food contact in federal meat and poultry establishments.

Test Data

Independent laboratory tests show 511 Porous Plus out performs competitive products. Test results are available upon request for Staining, Static Coefficient of Friction, Tabor Abrasion, Surface Absorption, Freeze/Thaw, and Vapor Transmission.

NOTE: For any questions concerning grout - refer to the grout manufacturers specifications. 511 Porous Plus will not stop acid etching.

Sample Testing

Due to the differences of each substrate, several inconspicuous test patches should be completed to assure maximum performance. User must determine suitability of the product for their intended use.

Color Enhancement

For added color with "Textured Nonpolished" surfaces, Mira Matte may be used. For porous type "Paver", Saltillo & Terra Cotta Paste & Liquid Wax may be used. Refer to individual label or product data sheet for more information.

Slip Resistance

511 Porous Plus increases the static coefficient of friction on all surfaces. 511 Porous Plus has been used successfully for compliance with the American Disability Act's recommendations for slip resistance (ASTM C 1028-89) on polished & honed surfaces.

Protection Section

Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non masonry surfaces.

New Installations - Application Instructions

Read entire label and PDS before using.

Before Grouting: Apply 511 Porous Plus to all surfaces prior to grouting. This step will allow quick and easy cleanup after grouting. Grout can stain many surfaces if this procedure is not used prior to the grouting process. Apply 511 Porous Plus using a MiraSeal™ Applicator or a clean towel. Apply enough to wet the surface. (See coverage charts) Be careful not to saturate the open grout joints. Allow 511 Porous Plus to stand for approximately 3-5 minutes for maximum penetration. Any excess sealer remaining at this time should be removed by wiping the surface with a clean dry towel. On very porous surfaces apply another application after the previous application has dried 2-3 hours. Allow 511 Porous Plus to cure for 12-24 hours before continuing with the grouting procedure.

After Grouting: Once grouted, make sure that all grout residue is removed from the surface with a clean sponge and water. Allow grout to dry at least 24-72 hours.

If grout clean up is not performed effectively, an additional cleaning may be necessary to remove remaining grout residue or haze. For this procedure use GCFR (Grout & Concrete Film Remover) or Epoxy Grout Film Remover following the instructions carefully. Once the area has completely dried, proceed with the sealing of the grout for water and stain resistance. Apply 511 Porous Plus to all grout with a thin paint brush. Any excess sealer that gets on the surface should be wiped off with a clean towel before it dries. On larger jobs grout can be sealed by retreating the entire area including the tile or stone surface a second time. Be careful not to allow the sealer to puddle or dry on presealed surfaces.

Existing Installation - Surface Preparation

Surface must be dry and free of contaminants, including previously applied sealers, dirt, lime & hard water deposits, efflorescence, rust & other heavy dirt and grime.

Floor Coating/Wax Removal: To remove existing coatings and/or waxes, use Mira Strip of H2O Strip following the instructions carefully.

Heavy Duty Cleaning: To remove lime and hard water deposits, efflorescence, rust and other heavy dirt and grime use GCFR (Grout & Concrete Film Remover) following the instructions carefully. Do not use GCFR on polished marble or acid sensitive surfaces. For a non-acid deep clean use Liquid Poulitce as directed. All strippers and/or cleaners should be thoroughly rinsed with clean water and the surface allowed to dry.

Existing Surfaces: Follow the application instructions previously mentioned, except now, seal the grout and tile or stone surfaces at the same time. When treating surfaces together, make sure that the recessed grout is saturated.

Cure Time

511 Porous Plus will be dry to the touch in 1-3 hours and may be used for normal foot traffic. For optimum results the area should be kept dry and free from staining materials for 24-72 hours.

Coverage Chart - used as directed

Material	Cost per sq.ft./sq.m.	500 sq.ft. 45 sq.m.	1000 sq.ft. 90 sq.m.	1500 sq.ft. 135 sq.m.	2000 sq.ft. 180 sq.m.
Sanded Grout	(.15-.28)				
Limestone	(.15-.28)				
Saltillo	(.15-.45)				
Sand Stone	(.15-.28)				
Flag Stone	(.15-.28)				
Flamed Granite	(.15-.28)				
Textured Marble	(.15-.28)				
Brick	(.15-.28)				
Concrete	(.15-.45)				
Stucco	(.22-.45)				
Slate	(.15-.28)				
Terra Cotta	(.15-.45)				
Cantera/Adoquin	(.15-.45)				
Masonry	(.15-.45)				
Polished Stone	Cost per sq. ft./3000-4000 sq.ft. (.05 - .07)				

Cost per sq. ft. is based on a suggested list price of \$225/gallon. 1 gallon = 3.785 liters.

Ongoing Maintenance

For ongoing maintenance instructions please refer to Miracle Sealants' Care Guides.

Storage

Store 511 Porous Plus in the original container, properly sealed to avoid contamination and solvent evaporation. Stored at 77° F (40° C), 511 Porous Plus will have a shelf life of 12 months.

Technical Support

For additional technical support, contact Miracle Sealants Company @ 1-800-350-1901 or 626-443-6433 ext. 3013

Office Hours

Monday - Friday from 8:30 am - 5:00 pm PT. 1-626-443-6433 1-800-350-1901 Fax: 1-626-443-1435 website: www.miraclesealants.com

Product Damaged During Transportation

If product is damaged during transportation contact Info Trac @ 1-800-535-5053

Additional Products

Miracle Sealants Company offers a complete line of water & stain repellents, sealers, cleaners, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it-yourself specialist

MiraSeal™ 511 Porous Plus

Natural Look Penetrating Sealer

Osha's Hazard Communication Standard U.S. Department Of Labor

29 CFR 1910.1200 OMB No. 1218-0072
Identity No: Name: 511 Porous Plus

Section 1

Manufacturers Name: Miracle Sealants Company
Address: 12318 Lower Azusa Road Emergency Phone: 800-350-1901
City: Arcadia State: CA Phone: 626-443-6433
Date Prepared: 08-01-2001

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components	CAS*	OSHA PEL	ACGIH TLV
Petroleum Distillate	64741-65-7	100ppm	150ppm
N-Heptane	142-82-5	500ppm	400ppm
Ethyl Acetate	141-78-6	400ppm	400ppm
Butyl Acetate	123-86-4	150ppm	150ppm

VOC: 760 g/L

Section 3 - Physical/Chemical Characteristics

Boiling Point: 320° F Specific Gravity: 0.80
Vapor Pressure: Not Tested Melting Point: Not Tested
Vapor Density: Not Tested Evaporation Rate: Not Tested
Solubility In Water: Insoluble
Appearance and Odor: Colorless, Solvent Odor

Section 4 - Fire And Explosion Hazard Data

Flash Point: 145° F Flammable Limits: Not Tested
LEL: Not Tested UEL: Not Tested
PH: Neutral DOT*: N/A
NFPA Hazard Rating H F R S (0-Least, 4-Extreme): 1 1 0 0
Extinguishing Media: Co2, Dry Foam
Special Fire Fighting Procedures: Combustible - Wear Full Bunker Gear And NIOSH Approved Breathing Apparatus.
Unusual Fire And Explosion Hazards: Cool Exposed Containers With Water To Prevent Rupturing. Heat Will Cause Phosgene Gas.

Section 5 - Reactivity Data

Stability: Stable
Conditions To Avoid: Keep Away From Heat, Flame & Sparks
Incompatible Materials To Avoid: Heat, Flames, Strong Oxidizer
Hazardous Polymerization: None
Hazardous Decomposition Product: CO2

Section 6 - Health Hazard Data

Routes of Entry:

Inhalation - Possible
Skin - Possible
Ingestion - Possible
Health Hazards - Same As Signs And Symptoms Of Exposure
OSHA Carcinogenicity - None; NTP - None; IARC Monographs - None

Signs and Symptoms of Over Exposure

Eyes: Burning Irritation
Skin: Slight Irritation, Deffating Of The Skin. Material Will Place A Clear Coating Onto Skin.
Ingestion: Toxic

Inhalation: Irritation, Dizziness, Headaches - High Vapor Concentration May Cause CNS Depression.

Medical Conditions Aggravated: Same As Signs And Symptoms Of Over Exposure.

Emergency And First Aid Procedures

Eyes: Flush With Water For 15 minutes. If Irritation Persists, Call Physician.
Skin: Wash With Soap And Water. If Irritation Persists, Call Physician.
Ingestion: Do Not Induce Vomiting. Call Physician. Keep Victim's Head Below Hips To Prevent Aspiration
Inhalation: Get Person To Fresh Air. If Unconscious, Call A Physician.

Section 7 - Precautions For Safe Handling And Use

Steps To Be Taken In Case Material Is Released Or Spilled: Soak Up With Inert, Absorbent Material. Scoop Up and Place In A Proper Disposal Container.

Waste Disposal Method: Dispose Of In Accordance With State and Local Regulations.

Precautions To Be Taken In Handling And Storing: Store In A Cool, Dry Place Out Of Direct Sunlight. Do Not Freeze or Heat Above 110° F

Other Precautions: KEEP OUT OF REACH OF CHILDREN. Follow directions on the container for proper use of this product.

Section 8 - Control Measures

Respiratory Protection: Open All Doors And Windows. Exposure Above The TLV Or PEL Require A NIOSH Approved Respirator Equipped For The Exposure Or Suitable Respiratory Protection Per 20 CFR 1910.34.

Ventilation

Local Exhaust - If Available Special - None
Mechanical - If Available Other - None

Protective Gloves: Rubber or Plastic, Chemical Resistant

Eye Protection: Tight Fitting, Splash Proof Safety Glasses or Goggles
Other Protective Clothing Or Equipment: Chemical Resistant Clothing.

Work Hygienic Practices: Wash Hand Thoroughly Before Handling Food Stuffs, Liquids or Tobacco Products. Use Common Sense And Care Around Chemicals. Never Mix Chemicals. Consult Your Supervisor For Other Practices. All Practices Depend On Your Specific Business. Directions For Use Normally Found On Label Which Will Dictate Engineering And Control Measures.

Section 9 - Shipping and Regulatory classification

DOT shipping Name:
DOT Hazard Class:
OSHA Hazard Class:
UN/NA Number:
EPA Hazard Waste: D 001, Ignitable
CPSC Classification: Combustible Liquid
Transportation Class: 55

Toxic Substances Control Act (TSCA): This Product And/Or All The Ingredients Contained In This Product Have Been Registered Under The Toxic Substances Control Act.

NOTE: Miracle Sealants believes the data set forth are accurate. Miracle Sealants makes no warranty with respects thereto and disclaims all liability or reliance thereon. Such data are offered solely for consideration, investigation and verification. Also, the data set forth is for the concentrated finished product. All lab samples are for experimental purposes only and used at the customers discretion.

WARRANTY & CAUTIONS

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealant Company shall be to replace such products proven to be defective. **Before using, user shall determine the suitability of the product for their intended use.** User assumes all risks and liability whatsoever in connection therein. Neither seller nor manufacturer shall be liable for any injury or inability to use this product.

Caution

511 Porous Plus contains combustible petroleum distillates. All solvents must be considered toxic and must be used in a well ventilated area. Good ventilation means that fresh air is flowing in such a way as to feel a slight breeze. Open windows and use fans to circulate air. Continue to ventilate until vapors are eliminated. Exposure to high vapor concentration must be avoided. Inhaling the vapors can be harmful. Keep away from heat and open flames. Avoid prolonged contact with skin. Gloves should be worn at all times. Keep small children and pets out of the area until product or surface has thoroughly dried. Refer to MSDS for additional information.